



JAPAN'S NO.1\* TRACTOR COMPANY

A

NeoStar -A211N (21HP Category)

This little master A211N , is a real workhorse with E-TVCS Engine. Suitable for interculture in narrow row crops.



2.98  
Ft.

Unmatched Width

2.1  
m

Turning Radius

4WD

4 Wheel Drive

SPECIFICATION

Model		NeoStar A211N - NS	NeoStar A211N - OP
Engine	Type	Kubota DI005-E4, E-TVCS, liquid-cooled, diesel engine	Kubota DI005-E4, E-TVCS, liquid-cooled, diesel engine
	No of cylinders	3	3
	Total displacement (CC)	1001	1001
	Maximum torque	58.3 N·m	58.3 N·m
Transmission	Clutch	Dry Single Plate	Dry Single Plate
	Steering	Manual Steering	Manual Steering
	Transmission	Gear shift, 9 forward and 3 reverse	Gear shift, 9 forward and 3 reverse
	Braking system	Oil immersed brakes (OIB)	Oil immersed brakes (OIB)
	Speed Range (Km/hr)	1.0-18.6	1.0-19.8
	Min. turning radius (with brake) (m)	2.1	2.1
Hydraulic Unit	Hydraulic control system	Position Control	Position Control & Super Draft Control
	Three point hitch	Category I	Category I
	Max. lift force At lift point (Kg)	750	750
PTO	PTO / Engine speed(rpm)	540 , 980	540 , 980
Capacities	Fuel tank	23 L	23 L
Dimensions	Overall length (without 3P) (mm)	2390	2410
	Overall width (mm)	910, 1000	1015, 1105
	Overall height (Top of steering wheel) (mm)	1260	1280
	Wheel base (mm)	1560	1560
	Min. ground clearance (mm)	285	325
	Weight (Kg)	600	630
Tires	Front (mm)	5-12	7-12 (180/85D12)
	Rear (mm)	8 - 18	8.3-20

CROP RANGE



Quality you can trust on

Kubota received the Deming Prize which is the highest proof of recognition of major advances in quality improvement. Kubota has also received the ISO9001 Certification which is the international standard of quality management systems, the ISO14001 Certification which is the international standards related to environment management, and the OSHAS 18001 Certification which is the international assessment series of occupational health and safety systems.

The Deming Prize

OSHAS 18001 Certification

ISO9001 Certification

ISO14001 Certification

Calculated according to our criteria. The actual capacity you achieve may be different. The specifications, information, and appearance of the machines herein are subject to change without notice.

Kubota Agricultural Machinery India Pvt Ltd.  
No.94, TVH BELICIAA, TOWER- 1,  
8<sup>th</sup> floor, MRC Nagar, Chennai - 600 028  
Tel : +91 - 44 - 6104 1500 Fax : 044 6104 1600  
Web : www.kubota.co.in, Follow Us :

Toll Free : 1800 309 1694

KUBOTA/ FEBRUARY 2023/ ENGLISH

\*Disclaimer: A per Japan's Journal GYOKAI, Kubota ranks No.1 (Agri Machinery) for the year 2021 in turnover  
\*Terms and conditions apply



# Worried about Narrow Fields?

Solution is right here, Kubota A211N  
Specially made of intercultural crops, with  
Unmatched width of 3 Feet

KRX 71 Specifications	
Attachment	Normal 3P
Overall Width	900 mm
Actual Cultivation Width	716 mm
Kind of Blade	L Blade
No of Flange	4
No of Blade on 1 Flange	4
Total Blades	16
Weight	156 Kg



## A211N KUBOTA Rotary Tiller KRX 71

## The Little Master - A211N

FOUR WHEEL DRIVE TRACTOR WITH JAPANESE  
TECHNOLOGY AND SUPERIOR PERFORMANCE

- Ample space for driving comfort,
- More working hours with less fatigue.



### Easy Maintenance

Full open bonnet helps for  
easy maintenance at any time.



### Reliable Diesel Engine


- E-TVCS, Liquid cooled, 3 cylinder diesel engine
- Better pickup, and higher torque



### Transmission

- DST-Type Clutch (Diaphragm Spring Type)
  - Less Wear and tear
  - Less Noise and vibration compared to conventional Clutch
- 9 forward and 3 reverse gears
- Max speed upto 18.9 km
- Dual Speed PTO 540 rpm & 980 rpm

### Ease of Working



Best Ground Clearance of 300mm  
910 mm rear width ,2.1 m turning radius  
easy maneuverability in narrow farms,  
is most suitable for inter cultivation.

### 4 x 4 Driving System

- 4WD Tractor have more traction and driving power, which makes work proceed more efficiently
- 4WD helps Faster cultivation, Quick planting time, lesser soil compaction resulting in increase yield and profit Compared to 2WD tractor

